

Evaluating GSM A5/1 security on hopping channels

Bogdan Diaconescu

v1.2

This paper is a practical approach on evaluating A5/1 stream cipher on a GSM hopping network air interface called Um. The end goal is to evaluate how easy is to break A5/1 with COTS hardware and open source software.

What this paper is NOT about: a full description of GSM standard and A5/1 stream cipher.

About GSM hopping channels.

This work is based on the previous work that resulted in Airprobe being able to decode the GSM logical channels when a capture of IQ data is provided for a specific ARFCN. We modified Airprobe to support hopping channels by taking IQ data samples from files corresponding to each ARFCN of interest.

GSM slow frequency hopping is intended to reduce the adjacent cells interference by switching between a set of ARFCNs that are orthogonal to the set used by own cell. The whole set of ARFCNs used by the cell is broadcast by BTS on BCCH channel in SI Type 1 message and the hopping parameters are sent from BTS to MS in an RR Immediate assignment message.

Method used for frequency hopping:

1. Capture spectrum so that all the needed ARFCNs for hopping will be included into the bandwidth.
2. Channelize and downsample the spectrum in order to obtain a data stream for each needed ARFCN. A PFB (Poliphase Filter Bank) is used for that.
3. Identify your call and in turn identify the hopping parameters.
4. Feed the modified gsm-receiver from airprobe with the hopping parameters.
5. Run the same steps as in the case of non hopping cell. For traffic channel there could be a different set of hopping parameters.

Prerequisites: Use USRP N210 or USRP2 from Ettus. For this work USRP N210 has been used. It can acquire 25Mhz bandwidth from the spectrum without any FPGA changes or other software changes on PC.

Step 1: Capture the data on the main ARFCN

The main ARFCN for the cell would be the one with them maximum signal strength and this can be determined with kal tool [Ref 4]

```
sudo kal -s GSM900
```

```
kal: Scanning for GSM-900 base stations.
```

```
chan: 33 (941.6MHz + 234Hz) power: 10791.92
```

Therefore I have my main cell physical channel on ARFCN 33 and in turn the parameters for the engine needs to be set in *capture_decode_channelize2.sh*:

```
CONFIGURATION=""0B"
```

```
CA=""33"
```

```
C0=""33"
```

```
MA=""01"
```

```
# This needs to be less or equal than the number of channels in CA
```

`./capture_decode_channelize2.sh > out.txt` will produce the data streams for channel 33 and output of decoded messages in Wireshark.

Step 2: Get all CA channels and determine cell hopping parameters for the call

Determine Cell Allocation(CA) from System Information Type 1: 12 22 33 42 49 54

The screenshot shows the Wireshark interface with the following details:

- Filter:** Expression... Clear Apply Save
- Packet List:**

No.	Time	Source	Destination	Protocol	Length	Info
120	2.738997000	127.0.0.1	127.0.0.1	GSMTAP	81	(CCCH) (RR) Paging Request Type 1
121	2.766104000	127.0.0.1	127.0.0.1	GSMTAP	81	(CCCH) (RR) Paging Request Type 1
122	2.784147000	127.0.0.1	127.0.0.1	GSMTAP	81	(CCCH) (RR) Paging Request Type 1
123	2.815724000	127.0.0.1	127.0.0.1	GSMTAP	81	(CCCH) (RR) System Information Type 1
124	2.833770000	127.0.0.1	127.0.0.1	GSMTAP	81	(CCCH) (RR) System Information Type 13
125	2.860876000	127.0.0.1	127.0.0.1	GSMTAP	81	(CCCH) (RR) Paging Request Type 1
- Packet Details (Packet 123):**
 - ..00 0000 0000 0000 = ARFCN: 0
 - .0.. = Uplink: 0
 - Signal/Noise Ratio (dB): 0
 - Signal Level (dBm): 0
 - GSM Frame Number: 640565
 - Channel Type: BCCH (1)
 - Antenna Number: 0
 - Sub-Slot: 0
 - GSM CCCH - System Information Type 1**
 - L2 Pseudo Length
 - Protocol Discriminator: Radio Resources Management messages
 - Message Type: System Information Type 1
 - Cell Channel Description
 - 00.. 000. = Format Identifier: bit map 0 (0x00)
 - List of ARFCNs = 54 49 42 33 22 12
 - RACH Control Parameters
 - SI 1 Rest Octets
- Packet Bytes:**

```

0000 00 00 00 00 00 00 00 00 00 00 00 00 08 00 45 00 .....E.
0010 00 43 46 7e 40 00 40 11 f6 29 7f 00 00 01 7f 00 .CF~@.@. .).....
0020 00 01 9f 40 12 79 00 2f fe 42 02 04 01 00 00 00 ...@.y/.B.....
0030 00 00 00 09 c6 35 01 00 00 00 55 06 19 00 00 00 .....5..U.....

```

Then next step is to determine SDCCH channel Timeslot and hopping parameters from Immediate Assignment message: channel Timeslot=1; Subchannel=0; MAIO=0; HSN=2; MA=07

Now run again the script in order to obtain all channels:

```

CONFIGURATION="0B"           # Timeslot 1
CA="12 22 33 42 49 54"      # Cell Allocation in increasing order
C0="33"                     # C0 ARFCN
MA="07"                     # Mobile Allocation – ARFCNs used for this channel

```

```

MAIO=0                # Mobile Allocation Index Offset
HSN=2                 # Hopping Sequence Number
KEY="00 00 00 00 00 00 00 00"

```

```
./capture_decode_channelize2.sh > out.txt
```

File Edit View Go Capture Analyze Statistics Telephony Tools Internals Help

Filter: Expression... Clear Apply Save

No.	Time	Source	Destination	Protocol	Length	Info
147	3.366545000	127.0.0.1	127.0.0.1	GSMTAP	81	(CCCH) (RR) Immediate Assignment
148	3.384593000	127.0.0.1	127.0.0.1	GSMTAP	81	(CCCH) (RR) Paging Request Type 1
149	3.411709000	127.0.0.1	127.0.0.1	GSMTAP	81	(CCCH) (RR) Immediate Assignment
150	3.429758000	127.0.0.1	127.0.0.1	GSMTAP	81	(CCCH) (RR) Paging Request Type 1
151	3.456874000	127.0.0.1	127.0.0.1	GSMTAP	81	(CCCH) (RR) Paging Request Type 1
152	3.474932000	127.0.0.1	127.0.0.1	GSMTAP	81	(CCCH) (RR) Paging Request Type 1

▶ Protocol Discriminator: Radio Resources Management messages
 Message Type: Immediate Assignment
 ▶ Page Mode
 ▶ Dedicated mode or TBF
 ▼ Channel Description
 0100 0... = SDCCH/8 + SACCH/C8 or CBCH (SDCCH/8), Subchannel 0
001 = Timeslot: 1
 110. = Training Sequence: 6
 ...1 = Hopping channel: Yes
 Hopping channel: MAIO 0
 Hopping channel: HSN 2
 ▶ Request Reference
 ▶ Timing Advance
 ▼ Mobile Allocation
 Length: 1
Bitmap of increasing ARFCNs included in the Mobile Allocation: 11100000
 ▶ IA Rest Octets

0030 00 00 00 09 c6 af 02 00 00 00 31 06 3f 00 41 d01.?A.
 0040 02 f2 18 79 01 01 07 2b 2b 2b 2b 2b 2b 2b 2b ...y..+ +++++++
 0050 2b +

○ Text item (text), 1 byte ≡ Packets: 541 Displ... ≡ Profile: Default

Step 3: Decode the SDCCH channel

```

CONFIGURATION="1S"      # Timeslot 1
CA="12 22 33 42 49 54" # Cell Allocation in increasing order
C0="33"                 # C0 ARFCN
MA="07"                 # Mobile Allocation – ARFCNs used for this channel
MAIO=0                  # Mobile Allocation Index Offset
HSN=2                   # Hopping Sequence Number
KEY="00 00 00 00 00 00 00 00" # KC – zero for now

```

`./capture_decode_channelize2.sh > out.txt`

will produce Wireshark data for the frames that can be decoded and the rest of the data in out.txt.

Note: gsm-receiver will produce output for all the sub-slots currently on the SDCCH so it will be useful to filter the messages in Wireshark based on the known sub-slot from the Immediate Assignment command. In our case the sub-slot value is 0.

The screenshot shows the Wireshark interface with the following details:

- Filter: `gsmtap.sub_slot==0`
- Table of captured frames:

No.	Time	Protocol	Length	Info
9	3.430269000	LAPDm	81	U, func=UI(DTAP) (RR) System Information Type 6
10	3.517773000	LAPDm	81	U, func=UI
12	3.753124000	LAPDm	81	U F, func=UA(DTAP) (MM) CM Service Request
13	3.901189000	LAPDm	81	U, func=UI(DTAP) (RR) System Information Type 5
15	3.989026000	LAPDm	81	I, N(R)=1, N(S)=0(DTAP) (RR) Classmark Enquiry
17	4.225851000	LAPDm	81	I, N(R)=1, N(S)=1(DTAP) (MM) Authentication Request
18	4.374474000	LAPDm	81	U, func=UI(DTAP) (RR) System Information Type 5ter
22	4.697638000	LAPDm	81	S, func=RR, N(R)=3
26	4.845566000	LAPDm	81	U, func=UI(DTAP) (RR) System Information Type 6
29	4.933395000	LAPDm	81	I, N(R)=3, N(S)=2(DTAP) (RR) Ciphering Mode Command

The detailed view of frame 29 shows:

- .0.. = Uplink: 0
- Signal/Noise Ratio (dB): 0
- Signal Level (dBm): 0
- GSM Frame Number: 640697
- Channel Type: SACCH/8 (136)
- Antenna Number: 0
- Sub-Slot: 0
- ▼ SACCH L1 Header, Power Level: 5, Timing Advance: 1
 - ...0 0101 = MS power level: 5
 -1.. = FPC: In use
 - Actual Timing Advance: 1
- ▶ Link Access Procedure, Channel Dm (LAPDm)
- ▶ GSM A-I/F DTAP - System Information Type 6

The packet bytes pane shows the following hex data:

```
0030 00 00 00 09 c6 b9 88 00 00 00 05 01 03 03 2d 06 ..... ..-..
0040 1e 81 a7 22 f6 10 2b 83 93 ff 2b 2b 2b 2b 2b 2b ...".+. .+++++
0050 2b
```

The RR Ciphering Mode Command is the last message sent in clear text before the encryption is enabled. The encrypted bursts are to be found in out.txt in the form

Cx 488134 754090:

0111000110001101110001110001110001100011000101100011100111100001010011110101010101...

Px 488134 754090:

011100011000110111000111000110001100011000101100011100111100001010011110101010101...

Sx 488134 754090:


```

100010110101000001010011001101011001001100010001000111110010100000101111110100010010100011
10110100100001000011001
##### Found potential key (bits: 22)#####
251f71485a37e2af -> 251f71485a37e2af
Framecount is 754765
KC(0): 2f ce 35 dc 3e 09 20 3c mismatch
...
KC(30): 49 b2 90 6c 98 5f ce 2b mismatch
KC(31): 88 0b 84 cd 8f 24 74 00 *** MATCHED ***

```

Now changing the KEY="00 00 00 00 00 00 00 00" to KEY="88 0b 84 cd 8f 24 74 00" and running again `./capture_decode_channelize2.sh > out.txt` will reveal the messages on SDCCH after the ciphering started:

The screenshot displays the Wireshark interface with the following details:

- Filter:** `gsmtap.sub_slot==0`
- Packet List:**

No.	Time	Protocol	Length	Info
1	0.000000000	LAPDm	81	U, func=UI
2	0.148808000	LAPDm	81	U, func=UI(DTAP) (RR) System Information Type 5
3	0.237061000	LAPDm	81	S, func=RR, N(R)=4
4	0.473744000	LAPDm	81	S, func=RR, N(R)=5
5	0.622227000	LAPDm	81	U, func=UI(DTAP) (RR) System Information Type 5ter
6	0.710396000	LAPDm	81	I, N(R)=5, N(S)=3(DTAP) (CC) Call Proceeding
7	0.945963000	LAPDm	81	I, N(R)=5, N(S)=4 (Fragment)
8	1.094512000	LAPDm	81	U, func=UI(DTAP) (RR) System Information Type 6
9	1.182320000	LAPDm	81	I, N(R)=5, N(S)=5(DTAP) (RR) Assignment Command
- Packet Details (Packet 9):**
 - Channel Description - Description of the first channel, after time
 - 0000 1... = TCH/F + FACCH/F and SACCH/F
 -111 = Timeslot: 7
 - 110. = Training Sequence: 6
 - ...1 = Hopping channel: Yes
 - Hopping channel: MAIO 2
 - Hopping channel: HSN 2
 - Power Command
 - Frequency List - Frequency List, after time
 - Element ID: 5
 - Length: 16
 - 00.. 000. = Format Identifier: bit map 0 (0x00)
 - List of ARFCNs = 33 22 12
 - Channel Mode - Mode of the First Channel(Channel Set 1)
- Packet Bytes:**

```

0000 06 2e 0f d0 82 05 05 10 00 00 00 00 00 00 00 00 .....
0010 00 00 00 01 00 20 08 00 63 01 ..... C.

```
- Frame (81 bytes) Reassembled LAPDm (26 bytes)**
- Text item (text), 16 bytes** Packets: 10 Displa... Profile: Default

From the decrypted SDCCH channel it is easy to observe the Assignment Command that is sent by the BTS to MS in order to assign the traffic channel. The important parameters are traffic channel Timeslot and hopping parameters for the traffic channel.

Note: the traffic channel can have different hopping parameters than SDCCH channel. Although the MA in this case is the same, it can be quite different than the MA used in the SDCCH channel.

Step 3: Decode the traffic channel

The saga continues with another run of `./capture_decode_channelize2.sh > out.txt`. This is necessary to decode the traffic channel and obtain the audio stream and the configuration is presented below. One could also see in Wireshark the SI messages sent on the FACCH channel that share the same Timeslot with TCH.

```
CONFIGURATION="7T"           # Timeslot 7 for traffic
CA="12 22 33 42 49 54"      # Cell Allocation in increasing order
C0="33"                     # C0 ARFCN
MA="07"                     # Mobile Allocation
MAIO=2                      # Mobile Allocation Index Offset
HSN=2                       # Hopping Sequence Number
KEY="88 0b 84 cd 8f 24 74 00" # KC
```

The screenshot displays the Wireshark network protocol analyzer interface. The top menu bar includes File, Edit, View, Go, Capture, Analyze, Statistics, Telephony, Tools, Internals, and Help. Below the menu is a toolbar with various icons for file operations and analysis. A filter field is present with the text 'Expression...' and buttons for 'Clear', 'Apply', and 'Save'. The main packet list pane shows a series of captured packets:

No.	Time	Protocol	Length	Info
7	1.910103000	LAPDm	81	U, func=UI(DTAP) (RR) System Information Type 5
8	2.395049000	LAPDm	81	U, func=UI(DTAP) (RR) System Information Type 5ter
9	2.873688000	LAPDm	81	U, func=UI(DTAP) (RR) System Information Type 6
10	3.352363000	LAPDm	81	U, func=UI(DTAP) (RR) System Information Type 5
11	3.831181000	LAPDm	81	U, func=UI(DTAP) (RR) System Information Type 5ter
12	4.029136000	LAPDm	81	I, N(R)=1, N(S)=0 (Fragment)
13	4.167334000	LAPDm/GSM	81	I, N(R)=1, N(S)=1(DTAP) (CC) Alerting (GSM MAP) invoke notify
14	4.310138000	LAPDm	81	U, func=UI(DTAP) (RR) System Information Type 6
15	4.788698000	LAPDm	81	U, func=UI(DTAP) (RR) System Information Type 5
16	5.267459000	LAPDm	81	U, func=UI(DTAP) (RR) System Information Type 5ter

The details pane for the selected packet (No. 16) shows the following information:

- GSM TAP Header, ARFCN: 0 (Downlink), TS: 7, Channel: FACCH/F (0)
- Version: 2
- Header length: 16 bytes
- Payload Type: GSM Um (MS<->BTS) (1)
- Time Slot: 7
- ..00 0000 0000 0000 = ARFCN: 0
- .0.. = Uplink: 0
- Signal/Noise Ratio (dB): 0
- Signal Level (dBm): 0
- GSM Frame Number: 642246
- Channel Type: FACCH/F (9)

The packet bytes pane shows the raw hex data of the frame, with a reassembled LAPDm payload of 24 bytes. The hex data is displayed in a grid format, with the first few bytes being 0000 0000 0000 0000 0000 0000 0000 0000 0000 0000 0800 4500. The reassembled LAPDm payload is shown as a single block of 24 bytes.

At this moment the voice stream will be found in speech.au.gsm file that can be listen with the following:

```
untoast speech.au.gsm
mplayer speech.au          # or other player
```

Conclusion:

1. The security of the GSM hopping channels is at the same level with the security of the non hopping channels, the only difference an attacker will encounter being the computing and storage resources needed to channelize and produce the data for each ARFCN.
2. We observed a very rapid degrading of the ability of Airprobe to correctly decode the GSM messages when the overall SNR degrades under -60dB for C0 channel, making necessary for a better demodulator.
3. The L1 header of the known plaintext (SI message) could change in both MS power level when FPC is in use and Timing Advance when MS is moving. Therefore some prediction is necessary to be used in

order to correctly guess the known plain text.

References:

1. **Airprobe git:** [git://git.gnumonks.org/airprobe.git](https://git.gnumonks.org/airprobe.git)
2. **Hopping channels description GSM 05.02 chapter 6**
3. https://srlabs.de/decrypting_gsm/
4. **Kal tool git:** [git://github.com/ttsou/kalibrate-uhd.git](https://github.com/ttsou/kalibrate-uhd.git)
5. <https://lists.srlabs.de/pipermail/a51/2010-July/000688.html>
6. **Airprobe-hopping.git:** <https://github.com/BogdanDIA/airprobe-hopping>